



## Building a Deck:

Decks are an extension of the main dwelling unit and as such must be designed and constructed to withstand all superimposed loads. The structure, supports, guards and stairs are regulated by the Ontario Building Code and setbacks to all property lines are regulated by provisions of the Town of Bradford West Gwillimbury Zoning By-Law.

A building permit is required for constructing a deck greater than 10m<sup>2</sup> (107 sq. ft.) or that is attached to the house.

In order to obtain a building permit, a completed building permit application accompanied by two sets of construction drawings and a copy of the property survey must be submitted to the Building Division at 3543 Line 11, Bradford.

The submission of a Building Permit Application shall consist of:

1. Two copies of the site plan based on a recent survey, showing the location of the deck with proximity to all property lines, location of all structures on the property.
2. Two copies of the floor plans showing the size and spacing of the footing piers, size, spans and direction of beams, floor joists and decking.
3. Two copies of elevations showing the height of the deck, depth of footings, height and construction of guards, handrails and stairs, cross-section detail illustrating the connection of the deck to the house.

Homeowners are permitted to prepare their own designs if they can demonstrate compliance with the requirements of the Ontario Building Code. Any designer other than the owner, who prepares and takes responsibility for the design of the deck, must possess the mandatory technical qualifications prescribed under the Ontario Building Code.

### Guards:

A guard is required when the difference in deck elevation above the finished grade exceeds 600mm (23 5/8").

Construction of guards must conform to the requirements of the Supplementary Standard SB-7 of the Ontario Building Code 2006.

### Proprietary Products and Materials:

Composite decking and guard systems must have Building Materials Evaluation Commission (BMEC) approval to be permitted for construction use in Ontario. Steel, aluminum and glass railing systems must be designed in accordance with structural requirements of Part 4 (Division B) of the Ontario Building Code.

### Deck Blocks:

Recent changes to the Ontario Building Code resulted in provisions that allow the use of deck blocks for construction of decks where:

- The deck is not attached to the house,
- Deck is not greater than 55m<sup>2</sup> (592 ft<sup>2</sup>),
- The difference in deck elevation above the finished grade exceeds 600mm (23 5/8"),
- The deck does not support a roof.


### Mandatory Inspections:

Once the permit is obtained all work must be inspected at key stages of construction to ensure that construction is in accordance with the permit drawings and complies with the Ontario Building Code;

1. **Footing Inspection:** holes are inspected to verify the depth, diameter and spacing of the piers prior to placement of concrete.
2. **Framing Inspection:** carried out at completion of framing components including the connection to the house.
3. **Final Inspection:** required at the time of completion of the deck flooring, guards and stairs.

To arrange for an inspection, please contact the Building Division by phone (905) 775-5369 ext. 1500, by fax (905) 778-4343, or in person at 3541 Line 11, Bradford. Please reference the building permit number, project address, required inspection date, contact name and phone number.

**While 48 hours notice is required, next day service can usually be achieved.**





**SITE PLAN**  
SCALE 1" = 15'-0"

Bradford  
west  
Gwillimbury

**Sample Site Plan**

A Growing Tradition




**TACBOC**  
STANDARD DETAIL

TITLE  
**WOOD DECK**  
FIXED TO SOLID MASONRY FOUNDATION WALL  
PLAN & SECTION


DWG. NO.

**D01a**

2007



SECTION 'A'




**TACBOC**  
STANDARD DETAIL

n7LE  
WOOD DECK  
FIXED TO BRICK VENEER & WOOD FRAMING  
PLAN & SECTION


DWG. NO.

D01b


2007



SECTION 'B'



BRACING PARALLEL TO BEAM



BRACING PERPENDICULAR TO BEAM

FREE STANDING DECKS GREATER THAN 600mm ABOVE GRADE SHALL RESIST LATERAL LOADINGS & MOVEMENT. ALL POSTS MUST BE BRACED WHERE THE SUPPORTED AREA EXCEEDS THOSE LISTED IN THE TABLE ON DO1d

**TACBOC**  
STANDARD DETAIL

TITLE  
WOOD DECK  
STAIR SECTION  
LATERAL SUPPORT FOR FREE STANDING DECKS

DWG. NO.

DO1c

2007

**POSTS SUPPORTING DECK & ROOF**

POST SIZE (mm)	MAXIMUM HEIGHT (M) SEE NOTE 7	SUPPORTED ROOF AREA (M <sup>2</sup> )				
		ROOF SNOW LOAD (kPa)				
		1.0	1.5	2.0	2.5	3.0
89x89	1.0	6.65	5.91	5.32	4.83	4.43
	1.5	3.63	3.23	2.90	2.64	2.42
	2.0	1.93	1.71	1.54	1.40	1.28
140x140	2.0	8.38	7.45	6.70	6.09	5.58
	2.5	5.72	5.08	4.57	4.15	3.80
	3.0	3.89	3.46	3.11	2.83	2.59
	3.5	2.70	2.40	2.16	1.96	1.80

**POSTS SUPPORTING DECKS**

POST SIZE (mm)	MAXIMUM HEIGHT (M) SEE NOTE 7	SUPPORTED DECK AREA (M <sup>2</sup> )				
		ROOF SNOW LOAD (kPa)				
		1.0	1.5	2.0	2.5	3.0
89x89	1.0	10.86	10.86	10.43	8.71	7.48
	1.5	5.93	5.93	5.69	4.76	4.09
	2.0	3.15	3.15	3.02	2.53	2.17
140x140	2.0	13.67	13.67	13.13	10.98	9.43
	2.5	9.32	9.32	8.96	7.48	6.43
	3.0	6.35	6.35	6.10	5.10	4.38
	3.5	4.41	4.41	4.23	3.54	3.04

JOIST SPAN (mm)	JOIST SIZE	PIER SIZE (mm)				BEAM SIZE				
		PIER SPACING (mm)				PIER SPACING (mm)				
		1200	1800	2400	3000	1200	1800	2400	3000	
75 kPa	1800	200φ	250φ	300φ	350φ	2/38x140	2/38x140	2/38x184	2/38x235	38x140
	2400	250φ	300φ	350φ	400φ	2/38x140	2/38x184	2/38x235	2/38x286	38x140
	3000	300φ	350φ	400φ	450φ	2/38x140	2/38x184	2/38x235	2/38x286	38x184
	3660	300φ	350φ	400φ	450φ	2/38x140	2/38x184	2/38x235	2/38x286	38x235
120 kPa	1800	200φ	200φ	250φ	250φ	2/38x140	2/38x140	2/38x184	2/38x235	38x140
	2400	200φ	250φ	250φ	300φ	2/38x140	2/38x184	2/38x235	2/38x286	38x140
	3000	200φ	250φ	300φ	350φ	2/38x140	2/38x184	2/38x235	2/38x286	38x184
	3660	250φ	300φ	350φ	350φ	2/38x140	2/38x184	2/38x235	2/38x286	38x235
190 kPa	1800	200φ	200φ	200φ	200φ	2/38x140	2/38x140	2/38x184	2/38x235	38x140
	2400	200φ	200φ	200φ	250φ	2/38x140	2/38x184	2/38x235	2/38x286	38x140
	3000	200φ	200φ	250φ	300φ	2/38x140	2/38x184	2/38x235	2/38x286	38x184
	3660	200φ	250φ	300φ	300φ	2/38x140	2/38x184	2/38x235	2/38x286	38x235

**GENERAL NOTES**

- SITE PLAN OR SURVEY IS REQUIRED SHOWING ALL LOT LINES & DIMENSIONS SIZE & LOCATION OF ALL EXISTING BUILDINGS, LOCATION & SIZE OF DECK
- LUMBER NO. 2 SPF OR BETTER, WOOD POSTS MIN. 89x89 (SOLID). USE CORROSION RESISTANT SPIRAL NAILS OR SCREWS.
- DECK IS NOT PERMITTED TO BE SUPPORTED ON BRICK VENEER
- CONCRETE PIERS SHALL BEAR ON UNDISTURBED SOIL. THE BEARING CAPACITY OF THE SOIL SHALL BE DETERMINED PRIOR TO CONSTRUCTION
- PROVIDE A HANDRAIL 900mm HIGH ON STAIRS IF MORE THAN THREE RISERS.
- FOR SUPPORTED AREAS WHICH EXCEED THOSE LISTED IN THESE TABLES THE POSTS SHALL BE BRACED AS SHOWN ON DOIC
- MAXIMUM HEIGHT REFERS TO THE HEIGHT OF THE POST FROM THE TOP OF THE PIER TO THE DECK SURFACE


**TACBOC**  
STANDARD DETAIL

TITLE  
**WOOD DECK**  
TABLES & NOTES


DWG. NO.

**DOLD**


2007




**PLAN**



**AXONOMETRIC**



**FRONT ELEVATION**




**SIDE ELEVATION**


**Notes:**

1. The top rail must be continuous. Use Detail EA-5 at the end spans, where continuity ends.


MAXIMUM SPAN OF RAIL BETWEEN POSTS	
Species	Maximum Span, m (ft-in)
Douglas Fir-Larch, Hem-Fir, Spruce-Pine-Fir	1.52 (5'-0")
Northern Species	1.52 (5'-0")
Column 1 ~	2




**Detail EA-1**  
**Exterior Connection: Top Rail Nailed to Post**




**PLAN**



**AXONOMETRIC**



**FRONT ELEVATION**



**SIDE ELEVATION**

**Notes:**


1. Decking is omitted from the plan view and the axonometric view for clarity.
2. Fasten 25 mm x 140 mm (5/8" x 6" nominal) outer deck board to rim joist with 63 mm (2 1/2") nails at 300 mm (12").
3. Fasten 25 mm x 140 mm (5/8" x 6" nominal) outer deck board to floor joist with 1 - 63 mm (2 1/2") nail at each joist.
4. The post may be positioned anywhere between the joists.
5. #9 screws may be replaced by #8 screws if the maximum spacing between posts is not more than 1.20 m (3'-11").
6. Dimensions shown are in mm unless otherwise specified.

MAXIMUM SPACING BETWEEN POSTS	
Species	Maximum Spacing, m (ft-in)
Douglas Fir-Larch, Hem-Fir, Spruce-Pine-Fir	1.56 (5'-1")
Northern Species	1.20 (3'-11")
Column 1	2




**Detail EB-2**  
**Exterior Connection: Post Screwed to Rim Joist**







PLAN



AXONOMETRIC



FRONT ELEVATION



SIDE ELEVATION

Note:

1. Dimensions shown are in mm unless otherwise specified.


Bradford  
west  
Gwillimbury




A Growing Tradition

**Detail EC-4**


**Exterior Connection: Infill Picket Screwed to Top Rail and Rim Joist**



PLAN



FRONT ELEVATION



AXONOMETRIC

SIDE ELEVATION

Notes:

1. Provide a suitable post, return, or solid support at each end of the guard.
2. Wood for cantilevered pickets shall be Douglas Fir-Larch, Spruce-Pine-Fir, or Hem-Fir Species.
3. Fasten rim joist to each floor joist with 3 - 82 mm (3 1/4") nails.
4. Dimensions shown are in mm unless otherwise specified.
5. The outer deck board shall not be less than 140 mm (6" nominal) wide. Where 38 mm (2" nominal) thick boards are used, the length of the wood screws shall be not less than 76 mm (3").


Bradford  
west  
Gwillimbury




A Growing Tradition

Detail ED-1


Exterior Connection: Cantilevered Picket Screwed to Rim Joist




**PLAN**



**AXONOMETRIC**



**FRONT ELEVATION**



**SIDE ELEVATION**

**Notes:**

1. Provide a suitable post, return, or solid support at each end of the guard.
2. Wood for cantilevered pickets shall be Douglas Fir-Larch, Spruce-Pine-Fir, or Hem-Fir Species.
3. Fasten rim joist to blocking with 3 - 82 mm (3 1/4") nails.
4. Dimensions shown are in mm unless otherwise specified.
5. Where 38 mm (2" nominal) thick boards are used, the length of the wood screws shall be not less than 76 mm (3").


**Bradford  
west  
Gwillimbury**




A Growing Tradition

**Detail ED-2**

**Exterior Connection: Cantilevered Picket Screwed to Rim Joist,  
Guard Parallel to Floor Joists**




PLAN TOP RAIL




AXONOMETRIC

ONE FASTENER IN HORIZONTALLY ORIENTATED PORTION OF TOP RAIL  
AND TWO IN VERTICALLY ORIENTATED PORTION.



FRONT TOP RAIL



SIDE TOP RAIL

**Notes:**

1. Screws fastening pickets are omitted for clarity.
2. Provide a minimum of 10 pickets beyond the return if end restraint of the guard is provided by this return detail only.

Bradford  
west  
Gwillimbury



A Growing Tradition

**Detail ED-5**  
**Exterior Connection: Corner Joint**